SAFETY DATA SHEET

Graphy

1. IDENTIFICATION

A. Product name

- TM-50

B. Recommended use and restriction on use

- General Use : UV-curable 3D printing material

- Restriction on use : Not available

C. Supplier information

- Company name : Graphy Inc.

- Address : 1607 Gasan SK V1 Center, 171, Gasan digital 1-ro, Geumcheon-gu, Seoul 08503

Korea

- Emergency telephone number : 82-2-864-3056

2. HAZARD IDENTIFICATION

A. GHS Classification

Skin corrosion/irritation : Category 2
Skin sensitization : Category 1
Acute aquatic toxicity : Category 3
Chronic aquatic toxicity : Category 3

B. GHS label elements

o Hazard symbols



o Signal word

- Warning

o Hazard statements

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H402 Harmful to aquatic organisms.
- H412 Harmful to aquatic life with long lasting effects

o Precautionary statements

1) Prevention

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection

2) Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P321 Specific treatment
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.

3) Storage

- Not applicable

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

C. Other hazards which do not result in classification: (NFPA Classification)

○ NFPA grade (0~4 level)

- Health: 2, Flammability: 0, Reactivity: 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | Trade Names and Synonyms | CAS No. | Content(%) |
|--------------------------------------|--------------------------|-------------|------------|
| Aliphatic Urethane Acrylate Oligomer | - | Proprietary | 40 ~ 60 |
| Proprietary Ingredient #1 | - | - | 5 ~ 20 |
| Proprietary Ingredient #2 | - | - | 20 ~ 40 |
| Photoinitiator | - | - | 1 ~ 10 |

4. FIRST AID MEASURE

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.
- Go to the hospital immediately if symptoms (flare, irritate) occur
- Wash thoroughly after handling.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.

D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Note to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHT MEASURES

A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Move containers from fire area, if you can do without the risk
- Avoid inhalation of materials or combustion by-products.
- Do not access if the tank on fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Move container to safe area from the leak area.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill: Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption
- Wipe off the solvent.
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces

7. HANDLING AND STORAGE

A. Precautions for safe handling

- Large spill: Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption
- Wipe off the solvent.
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces

B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Avoid direct sunlight.
- Keep in the original container.
- Keep sealed when not in use
- No open fire
- Collect them in sealed containers
- Store away from water and sewer

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o ACGIH TLV
 - Not available
- OSHA PEL
 - Not available

B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

C. Individual protection measures, such as personal protective equipment

Respiratory protection

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum
- Consider warning properties before use
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

o Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

o Hand protection

- Wear appropriate glove

o Skin protection

- Wear appropriate clothing.

o Others

- Not available

| A. Appearance | | |
|---|---|--|
| - Appearance | Liquid (viscous liquid) | |
| - Color | Yellowish | |
| B. Odor | Not available | |
| C. Odor threshold | Not available | |
| D. pH | Not available | |
| E. Melting point/Freezing point | Not available | |
| F. Initial Boiling Point/Boiling Ranges | Not available | |
| G. Flash point | Not available | |
| H. Evaporation rate | Not available | |
| I. Flammability (solid, gas) | Not available | |
| J. Upper/Lower Flammability or explosive limits | Not available | |
| K. Vapour pressure | Not available | |
| L. Solubility | Not available | |
| M. Vapour density | Not available | |
| N. Specific gravity(Relative density) | Not available | |
| O. Partition coefficient of n-octanol/water | Not available | |
| P. Autoignition temperature | Not available | |
| Q. Decomposition temperature | Not available | |
| R. Viscosity | $350 \sim 750 \text{ cps } (25 ^{\circ}\text{C})$ | |
| S. Molecular weight | Not available | |

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

C. Conditions to avoid

- Avoid: contact with incompatible materials and condition.
- Avoid: Accumulation of electrostatic charges, Heating, Flames and hot surfaces

D. Incompatible materials

- Not available.

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- (Respiratory tracts)Not available
- o (Oral)
 - Not available
- (Eye · Skin)
 - Cause skin irritation
 - May cause an allergic skin reaction

B. Delayed and immediate effects and also chronic effects form short and long exposure

o Acute toxicity

- * Oral
 - Product (ATEmix) : >5000mg/kg
 - [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate]: LD50 >5000 mg/kg Rat (OECD Guideline 401, GLP, ECHA)

- * Dental
 - Product (ATFmix) : >5000mg/kg
- * Inhalation
 - Product (ATFmix) : Not available
- Skin corrosion/irritation
 - Cause skin irritation
- o Serious eye damage/irritation
 - Not available
- o Respiratory sensitization
 - Not available
- O Skin sensitization
 - Not available
- o Carcinogenicity
 - * IARC
 - Not available
 - * 05H7
 - Not available
 - * ACGIH
 - Not available
 - * NTP
 - Not available
 - * EU CLP
 - Not available
- o Germ cell mutagenicity
 - Not available
- $\circ \ Reproductive \ toxicity$
 - Not available
- $\circ \ STOT\text{-single exposure}$
 - Not available
- o STOT-repeated exposure
 - Not available
- o Aspiration hazard
- Not available

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- o Fish
 - Not available
- o Crustaceans
 - [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate]: EC50 >1.2 mg/l 48 hr Daphnia magna (OECD Guideline 202, GLP, ECHA)
- o Algae
 - [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate] : EC50 >0.68 mg/l 72hr Other (ECHA)

B. Persistence and degradability

- o Persistence
 - [2-Propenoic acid, (5-ethyl-1, 3-dioxan 5-yl)methyl ester] : $\log \text{Kow} = 1.9 \text{ (ECHA)}$
 - [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate] : log Kow = 3 (Estimate)
- $\circ \ Degradability$

- Not available

C. Bioaccumulative potential

- o Bioaccumulative potential
 - Not available
- o Biodegration
 - [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate]: 22(%), 28 day (ECHA)

D. Mobility in soil

- [7,7,9(or 7,9,9)- Trimethyl-4, 13-dioxo-3, 14-dioxa-5, 12-diazahexadecane-1, 16-diyl 2-methyl-2-propenoate] : 1512 (Estimate)

E. Other adverse effects

- Not available

13. DISPOSURE CONSIDERATION

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.

B. Special precautions for disposal

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG)

- Not applicable

B. Proper shopping name

- Not applicable

C. Hazard Class

- Not applicable

D. IMDG Packing group

- Not applicable

E. Marine pollutant

- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- Air transport(IATA): This product is NOT classified as dangerous for IATA Transport.
- EmS FIRE SCHEDULE : Not available
- EmS SPILLAGE SCHEDULE: Not available

15. REGULATORY INFORMATION

A. National and/or international regulatory information

- o POPs Management Law
 - Not applicable
- $\circ \ Information \ of \ EU \ Classification$
 - * Classification
 - [Phenylbis(2,4,6-trimethylbenzoyl)phosphine oxide]: H317, H413

o U.S. Federal regulations

- * OSHA PROCESS SAFETY (29CFR1910.119)
 - Not applicable
- * CERCLA Section 103 (40CFR302.4)
 - Not applicable

- * EPCRA Section 302 (40CFR355.30)
 - Not applicable
- * EPCRA Section 304 (40CFR355.40)
 - Not applicable
- * EPCRA Section 313 (40CFR372.65)
 - Not applicable
- o Rotterdam Convention listed ingredients
 - Not applicable
- o Stockholm Convention listed ingredients
 - Not applicable
- o Montreal Protocol listed ingredients
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2019-09-02

C. Revision number and Last date revised

- 5 times, 2020-09-08

D. Others

- This SDS is prepared according to the Globally Harmonized System (GHS)