

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

## LOCTITE 3D 3955 1KG

SDS No. : 676630 V002.1 Revision: 17.03.2022 printing date: 20.03.2023 Replaces version from: 22.11.2021

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1. Product identifier** LOCTITE 3D 3955 1KG
- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Acrylate adhesive
- 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkeladhesives.com.

#### **1.4.** Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification (CLP):	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Tris(2-acryloxyethyl) isocyanurate

## Page 2 of 13

#### Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate

Signal word:	Danger
Hazard statement:	H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects.
Precautionary statement:	P273 Avoid release to the environment.
Prevention	P280 Wear protective gloves/eye protection.
Precautionary statement:	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# Following substances are present in a concentration >= 0,1% and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration  $\geq$  the concentration limit that are assessed to be a PBT, vPvB or ED.

## **SECTION 3: Composition/information on ingredients**

3.2. Mixtures

## Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Tris(2-acryloxyethyl) isocyanurate 40220-08-4 254-843-6 01-2120741502-64	50- 100 %	Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7 282-810-6 01-2119987994-10	0,1- < 1 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317		

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

#### Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

#### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable extinguishing media:** water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes.Wear protective equipment.Ensure adequate ventilation.Keep away from sources of ignition.

#### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Scrape up as much material as possible. Sweep up spilled material. Avoid creating dust. Store in a partly filled, closed container until disposal. Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed. 7.2. Conditions for safe storage, including any incompatibilitiesEnsure good ventilation/extraction.Keep container tightly sealed.Refer to Technical Data Sheet

**7.3. Specific end use(s)** Acrylate adhesive

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

**Occupational Exposure Limits** 

Valid for Great Britain

None

**Occupational Exposure Limits** 

Valid for Ireland

None

# Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value	Remarks			
	<b>^</b>	ŕ	mg/l	ppm	mg/kg	others	
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	aqua (freshwater)		0,00943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	aqua (intermittent releases)		0,0943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	sewage treatment plant (STP)		10 mg/l				
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	aqua (marine water)		0,000943 mg/l				
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	sediment (freshwater)				0,62 mg/kg		
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	sediment (marine water)				0,062 mg/kg		
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	Soil				0,118 mg/kg		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	aqua (freshwater)		0,00101 mg/l				
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	aqua (marine water)		0,000101 mg/l				
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	aqua (intermittent releases)		0,035 mg/l				
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	sediment (freshwater)				0,24 mg/kg		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	sediment (marine water)				0,024 mg/kg		
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	Soil				0,047 mg/kg		

#### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	Workers	inhalation	Long term exposure - systemic effects		1,65 mg/m3	
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	Workers	dermal	Long term exposure - systemic effects		2,3 mg/kg	
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	inhalation	Long term exposure - systemic effects		0,29 mg/m3	
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	oral	Long term exposure - systemic effects		0,08 mg/kg	
(2,4,6-Trioxo-1,3,5-triazine- 1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate 40220-08-4	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	Workers	dermal	Long term exposure - systemic effects		1,7 mg/kg	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	Workers	inhalation	Long term exposure - systemic effects		5,88 mg/m3	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	

#### **Biological Exposure Indices:** None

#### 8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Dust mask, P2 particle filter.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

#### Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state	solid
Delivery form	solid
Colour	black
Odor	acrylic
Explosive limits	Not applicable, Product is a solid.
Flash point	> 100 °C (> 212 °F); ASTM D3278
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid.
Viscosity, dynamic	950 mPa.s no method
0	
Density	1,10 g/cm3 no method
0	-
Relative vapour density:	Not applicable, Product is a solid.
-	

#### 9.2. Other information

Other information not applicable for this product

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Reacts with strong oxidants. Acids. Reducing agents. Strong bases.

#### **10.2.** Chemical stability

Stable under recommended storage conditions.

# 10.3. Possibility of hazardous reactions

See section reactivity

#### **10.4.** Conditions to avoid

Stable under normal conditions of storage and use.

#### **10.5. Incompatible materials**

See section reactivity.

## 10.6. Hazardous decomposition products

carbon oxides. Hydrocarbons nitrogen oxides Rapid polymerisation may generate excessive heat and pressure.

## **SECTION 11: Toxicological information**

## Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LD0	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphi nate 84434-11-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

## Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphi	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
nate 84434-11-7				

## Acute inhalative toxicity:

No data available.

#### Skin corrosion/irritation:

No data available.

#### Serious eye damage/irritation:

No data available.

## Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
Tris(2-acryloxyethyl)	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
isocyanurate		assay (LLNA)		Local Lymph Node Assay)
40220-08-4				
Ethyl phenyl(2,4,6-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
trimethylbenzoyl)phosphi	_	assay (LLNA)		Local Lymph Node Assay)
nate				
84434-11-7				

#### Germ cell mutagenicity:

No data available.

#### Carcinogenicity

No data available.

No data available.

## STOT-single exposure:

No data available.

#### STOT-repeated exposure::

No data available.

#### Aspiration hazard:

No data available.

#### 11.2 Information on other hazards

not applicable

# **SECTION 12: Ecological information**

#### General ecological information:

Do not empty into drains / surface water / ground water.

## 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	LC50	9,43 mg/l	96 h	Danio rerio (reported as Brachydanio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	LC50	1,89 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

## Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	EC50	158,3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	EC50	2,26 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Tris(2-acryloxyethyl)	EC50	25,7 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
isocyanurate					Growth Inhibition Test)
40220-08-4					
Tris(2-acryloxyethyl)	EC10	12,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga,
isocyanurate					Growth Inhibition Test)
40220-08-4					
Ethyl phenyl(2,4,6-	EC50	1,01 mg/l	72 h	Desmodesmus subspicatus	not specified
	LCSO	1,01 116/1	, 2 11	Desinodesinus subspicutus	not speemed
trimethylbenzoyl)phosphinate					
84434-11-7					

#### Toxicity to microorganisms

No data available.

## 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	not readily biodegradable.	aerobic	14,5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7		aerobic	< 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

## 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Tris(2-acryloxyethyl) isocyanurate 40220-08-4	1,85	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Ethyl phenyl(2,4,6- trimethylbenzoyl)phosphinate 84434-11-7	2,91	25 °C	EU Method A.8 (Partition Coefficient)

## 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
Tris(2-acryloxyethyl) isocyanurate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
40220-08-4	Bioaccumulative (vPvB) criteria.
Ethyl phenyl(2,4,6-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
trimethylbenzoyl)phosphinate	Bioaccumulative (vPvB) criteria.
84434-11-7	

## **12.6. Endocrine disrupting properties**

not applicable

#### 12.7. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

# **SECTION 14: Transport information**

	ADR	3077		
	RID	3077		
	ADN	3077		
	IMDG	3077		
	IATA	3077		
14.2.	UN proper	shipping name		
	ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tris(2-		
	RID	acryloxyethyl) isocyanurate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tris(2-		
	ADN	acryloxyethyl) isocyanurate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tris(2-		
	IMDG	acryloxyethyl) isocyanurate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Tris(2-		
	IATA	acryloxyethyl) isocyanurate) Environmentally hazardous substance, solid, n.o.s. (Tris(2-acryloxyethyl) isocyanurate)		
14.3.	Transport hazard class(es)			
	ADR	9		
	RID	9		
	ADN	9		
	IMDG	9		
	IATA	9		
14.4.	Packing gro	oup		
	ADR	III		
	RID	III		
	ADN	III		
	IMDG	III		
	IATA	III		
14.5.	Environme	ntal hazards		
	ADR	not applicable		
	RID	not applicable		
	ADN	not applicable		
	IMDG	Marine pollutant		
	IATA	not applicable		
14.6.	Special pre	cautions for user		
14.0.				

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):		
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):		
Persistent organic pollutants (Regulation (EU) 2019/1021):		
VOC content	< 3 %	
(2010/75/EC)		

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

Page 12 of 13

Not applicable Not applicable Not applicable

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

#### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.