

Safety data sheet

Page: 1/11

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

1. Identification

Product identifier

Ultrafuse® TPU 64D natural

Recommended use: 3D Printing, for industrial use only

Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Telephone: + 31 591 820 389

E-mail address: sales@basf-3dps.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

No need for classification according to GHS criteria for this product.

Label elements

Globally Harmonized System (GHS)

The product does not require a hazard warning label in accordance with GHS criteria.

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Other hazards

According to UN GHS criteria

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

Polymer based on: polyurethane, stabilizing agents, additives

Hazardous ingredients (GHS)

According to UN GHS criteria

No particular hazards known.

4. First-Aid Measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Keep patient calm, remove to fresh air. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, foam, dry powder

Special hazards arising from the substance or mixture

carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product. Reclaim for processing if possible. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Protection against fire and explosion:

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

The product is not an oxidizer, not self-combustible and not explosive.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Avoid extreme heat. Protect against moisture.

Storage stability:

Protect against moisture.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Form: filament Colour: transparent Odour: odourless

Odour threshold:

not applicable

6 - 8 pH value: (20 °C)

> 120 °C

softening temperature: boiling temperature:

The product is a non-volatile solid.

Flash point:

not applicable

Evaporation rate:

The product is a non-volatile solid.

not flammable Flammability:

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature: > 400 °C

Vapour pressure:

not applicable

Density: approx. 1,1 - 1,2 g/cm3

(20 °C)

approx. 1,1 - 1,2 Relative density:

(20 °C)

Relative vapour density (air):

not applicable

Solubility in water: insoluble

Partitioning coefficient n-octanol/water (log Kow):

not applicable

Self ignition: not self-igniting

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

> 230 °C

Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading can result in products of degradation being

given off.

Viscosity, dynamic:

not applicable

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Other information

Self heating ability: It is not a substance capable of

> spontaneous heating according to UN transport regulations class 4.2.

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Bulk density: 500 - 700 kg/m3

(20 °C)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

No conditions to avoid anticipated.

Incompatible materials

Substances to avoid: oxidizing agents

Hazardous decomposition products

Thermal decomposition products:

Prolonged thermal loading can result in products of degradation being given off.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

(by inhalation): The inhalation of dusts represents a potential acute hazard.

(dermal):No applicable information available.

Irritation

Experimental/calculated data:

Skin corrosion/irritation: May cause mechanical irritation.

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Serious eye damage/irritation: May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Poorly biodegradable.

Elimination information:

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Due to the product characteristics the test is impossible.

Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria.

Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Other ecotoxicological advice:

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

13. Disposal Considerations

Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

RID

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:

Not applicable
Not applicable
Not applicable

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

Environmental hazards: Special precautions for Not applicable None known

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Not applicable
Not applicable
Not applicable

Special precautions for

user

None known

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Ship Type:
Not evaluated
Not evaluated
Not evaluated
Not evaluated
Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Date / Revised: 15.04.2020 Version: 2.0

Product: Ultrafuse® TPU 64D natural

(ID no. 11124420/SDS_GEN_00/EN)

Date of print 21.03.2021

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.



Safety data sheet

Page: 1/11

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

1. Identification

Product identifier

Ultrafuse® TPU 64D black

Recommended use: 3D Printing, for industrial use only

Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Telephone: + 31 591 820 389

E-mail address: sales@basf-3dps.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

No need for classification according to GHS criteria for this product.

Label elements

Globally Harmonized System (GHS)

The product does not require a hazard warning label in accordance with GHS criteria.

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

Other hazards

According to UN GHS criteria

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

Polymer based on: polyurethane, stabilizing agents, additives

Hazardous ingredients (GHS)

According to UN GHS criteria

No particular hazards known.

4. First-Aid Measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water. Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Keep patient calm, remove to fresh air. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, foam, dry powder

Special hazards arising from the substance or mixture

carbon oxides

The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product. Reclaim for processing if possible. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Protection against fire and explosion:

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

The product is not an oxidizer, not self-combustible and not explosive.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: Avoid extreme heat. Protect against moisture.

Storage stability:

Protect against moisture.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

Exposure controls

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

Form: filament
Colour: black
Odour: odourless

Odour threshold:

not applicable

pH value: 6 - 8 (20 °C) softening temperature: > 120 °C

softening temperature: boiling temperature:

The product is a non-volatile solid.

Flash point:

not applicable

Evaporation rate:

The product is a non-volatile solid.

Flammability: not flammable

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature: > 400 °C

Vapour pressure:

not applicable

Density: approx. 1,1 - 1,2 g/cm3

(20 °C)

Relative density: approx. 1,1 - 1,2

(20 °C)

Relative vapour density (air):

not applicable insoluble

Solubility in water: insoluble Partitioning coefficient n-octanol/water (log Kow):

not applicable

Self ignition: not self-igniting

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

> 230 °C

Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading can result in products of degradation being

given off.

Viscosity, dynamic:

not applicable

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Other information

Self heating ability: It is not a substance capable of

spontaneous heating according to UN transport regulations class 4.2.

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

Bulk density: 500 - 700 kg/m3

(20 °C)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

No conditions to avoid anticipated.

Incompatible materials

Substances to avoid: oxidizing agents

Hazardous decomposition products

Thermal decomposition products:

Prolonged thermal loading can result in products of degradation being given off.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

Experimental/calculated data:

(oral):No applicable information available.

(by inhalation): The inhalation of dusts represents a potential acute hazard.

(dermal):No applicable information available.

Irritation

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

Experimental/calculated data:

Skin corrosion/irritation: May cause mechanical irritation.

Serious eye damage/irritation: May cause mechanical irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Poorly biodegradable.

Elimination information:

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: Due to the product characteristics the test is impossible.

Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria.

Other adverse effects

The product does not contain substances that are listed in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

Additional information

Adsorbable organically-bound halogen (AOX):

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

This product contains no organically-bound halogen.

Other ecotoxicological advice:

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

13. Disposal Considerations

Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number: Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Not applicable Not applicable Packing group: Environmental hazards: Not applicable None known Special precautions for

user

RID

Not classified as a dangerous good under transport regulations

UN number: Not applicable Not applicable UN proper shipping name: Not applicable Transport hazard class(es): Packing group: Not applicable Environmental hazards: Not applicable Special precautions for

user

None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number: Not applicable

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Ship Type:
Not evaluated
Not evaluated
Not evaluated
Not evaluated
Not evaluated

Date / Revised: 18.12.2019 Version: 1.0

Product: Ultrafuse® TPU 64D black

(ID no. 11124424/SDS_GEN_00/EN)

Date of print 21.03.2021

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.